

Model No. (PS-B)		312NY	315NY	312YNY	315YNY
Capacity		12KVA	15KVA	12KVA	15KVA
Input Voltage		3 $\phi$ 4W 220/380V		3 $\phi$ 3W 380V	
Output Voltage		3 $\phi$ 4W 127/220V		3 $\phi$ 3W 220V	
Input Range		$\pm 15\%$			
Output Accuracy		$\leq 1\%$			
Frequency		50/60Hz $\pm 5\%$			
Response Time		< 0.1 second			
Waveform Distortion		No distortion			
Power Factor		0.95~1			
Efficiency		$\geq 98\%$			
Overload		150% for 10 seconds			
Protection	High Voltage	Standard Feature (can be Various / Multi / Big range pre-set and LED displayed)			
	Low Voltage	Standard Feature (can be Various / Multi / Big range pre-set and LED displayed)			
	Phase Failure	Standard Feature (can be Various / Multi / Big range pre-set and LED displayed)			
	Overload	Standard Feature (input and output double protection)			
	Short Circuit	Standard Feature			
Bypass		Standard Feature			
Indicators	Power	Standard Feature			
	Voltage	Standard Feature			
	Abnormal	Standard Feature			
Environment		Temperature: 0°C~45°C Humidity: 0%~95% RH (Non-Condensing)			
Dimension WxHxD (cm)		36x63x58			