

Model No. (APS-)	3120 X/N	3150 X/N	3200 X/N	3250 X/N	3300 X/N	3400 X/N	3500 X/N	3600 X/N	3750 X/N	31000 X/N
Capacity (KVA)	120	150	200	250	300	400	500	600	750	1000
Voltage	X2 : 3 ϕ 3W 220V series X3 : 3 ϕ 3W 380V series X4 : 3 ϕ 3W 415V series N1 : 3 ϕ 4W 110/190V series N2 : 3 ϕ 4W 220/380V series (indicate phase voltage) N3 : 3 ϕ 4W 220/380V series (indicate line voltage)									
Input Range	Nominal Voltage: $\pm 15\%$ ($\pm 10\% \sim \pm 40\%$ can be customized)									
Frequency	50/60Hz $\pm 5\%$									
Output Accuracy	$\leq 1\%$									
Power Factor	0.95 ~ 1									
Efficiency	$\geq 98\%$									
Response Time	< 0.1 Second									
Waveform Distortion	No distortion									
Protection	High Voltage	Standard Feature (can be Various / Multi / Big range pre-set and LED displayed)								
	Low Voltage	Standard Feature (can be Various / Multi / Big range pre-set and LED displayed)								
	Phase Failure	Standard Feature (can be Various / Multi / Big range pre-set and LED displayed)								
Bypass	Standard Feature (with High / Low Voltage, Phase Failure, Instant Black-Out Protection at work)									
Indicators	Power	Standard Feature								
	Voltage	Standard Feature								
	Abnormal	Standard Feature								
Overload	150% for 10 seconds									
Environment	Temperature: 0°C ~ 45°C Humidity: 0% ~ 95% RH (Non-Condensing)									