Model No. (PSN-)		3150 X/N	3200 X/N	3250 X/N	3300 X/N	3400 X/N	3500 X/N	3600 X/N	3750 X/N	31000 X/N	31200 X/N	31500 X/N	
Capacity (KVA)		150	200	250	300	400	500	600	750	1000	1200	1500	
Voltage		X2 : 3ϕ 3W 220V series X3 : 3ϕ 3W 380V series X4 : 3ϕ 3W 415V series N1 : 3ϕ 4W 110/190V series N2 : 3ϕ 4W 220/380V series (Indicate phase voltage) N3 : 3ϕ 4W 220/380V series (Indicate line voltage)											
Input Range		±15% (±10%~±40% can be customized)											
Frequency		50/60Hz±5%											
Output Accuracy		≤1%											
Power Factor		0.95~1											
Efficiency		≥98%											
Response Time		< 0.1 Sec.											
Waveform Distortion		No distortion (the same with input waveform)											
Warning	High Voltage	Standard Feature (can be Various / Multi / Big range pre-set and LED displayed)											
	Low Voltage	Standard Feature (can be Various / Multi / Big range pre-set and LED displayed)											
	Phase Failure	Standard Feature (can be Various / Multi / Big range pre-set and LED displayed)											
Bypass		Standard Feature (with Phase Failure, High / Low Voltage warning function at work)											
Indicators	Power	Standard Feature											
			Standard Feature										
	Abnormal	Standard Feature											
Overload		150% for 10 seconds											
Environment		Temperature: 0°C~45°C Humidity: 0%~95% RH (Non-Condensing)											