

# 油入自冷式規格總表 Oil self-cooling Specification

KVA	200V Rated output Current(A)	380V Rated output Current(A)	400V Rated output Current(A)	Regulation Accuracy(±%)	Length (mm)	Width (mm)	Height (mm)	Weight (mm)
100	262	151	131	0.8~3可調	900	900	1450	900
150	394	227	197	0.8~3可調	1000	1000	1550	1000
200	525	303	263	0.8~3可調	1050	1050	1600	1300
250	656	380	328	0.8~3可調	1080	1080	1600	1400
300	789	456	394	0.8~3可調	1170	1170	1700	1600
350	919	532	459	0.8~3可調	1170	1170	1700	1700
400	1050	608	525	0.8~3可調	1270	1270	1870	1850
500	1312	760	656	0.8~3可調	1270	1270	1870	2000
600	1575	909	787	0.8~3可調	1360	1360	1870	2300
750	1968	1140	984	0.8~3可調	1420	1420	1900	3000
1000	2624	1515	1312	0.8~3可調	1510	1510	1900	3400
1250	3289	1899	1640	0.8~3可調	1700	1700	1900	4000
1500	3947	2279	1968	0.8~3可調	1810	1810	2050	5500
2000	5263	3038	2624	0.8~3可調	1900	1900	2050	5900
2500		3798	3280	0.8~3可調	2000	2200	2050	6300
3000		4558	3936	0.8~3可調	2000	2200	2250	7500
4000		6077	5248	0.8~3可調	2000	2400	2250	8200
5000		7596	6560	0.8~3可調	2000	2600	2250	9000